



# Polisher 9237CB 180mm(7")

## Elastomer bumper on gear housing

protects a precious surface, such as that of a car body, from damage and scratches.



Loop handle with elastomer soft grip



Variable speed control by dial

Rotation speed is adjustable to application.



Vent dust cover of screw-down type

prevents ingress of wool fibers.



- Double Insulation (9237CB)
- Variable Speed
- Constant Speed
- Soft Start

|                                |                                   |
|--------------------------------|-----------------------------------|
| <b>Continuous rating Input</b> | 1,200W                            |
| <b>Capacity</b>                | Pad: 180mm (7")                   |
| <b>No load speed (rpm)</b>     | 0-3,200                           |
| <b>Dimensions (L x W x H)</b>  | 431x198x187mm (17"x7-3/4"x7-3/8") |
| <b>Net Weight*</b>             | 3.4kg (7.5lbs)                    |
| <b>Power supply cord</b>       | 2.5m(8.2ft)                       |



**Standard Equipment :** Loop handle or Side grip, Accessory set

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.



**Makita New Zealand Ltd.**  
15 Orbit Drive, Mairangi Bay  
PO Box 100 914, North Shore,  
Auckland 0745  
Fax 0800 600 601 Sales 09 4798251

Visit our website for information and tool features :  
[www.makita.co.nz](http://www.makita.co.nz)