



Easy-to-operate

PADDLE TYPE SWITCH



Durable motor with high heat resistance

High power & Heavy-Duty motor

Field with superior wiring technology leads to higher wattage without motor-size expansion.

The successors inherit slim body, zigzag varnish-coating on armature and powder vanish-coating on field from the predecessors.







Powder vanish-coating






Toolless Wheel Cover

More Durable Gears and Bearings

- · Gears are lubricated by securely sealed grease in gear room.
- · Bearings are protected from dust/dirt by Labyrinth construction.



Easy-to-operate paddle type on/off switch

- · Can be easily controlled by the hand gripping the machine.
- With non-slip pattern on the surface of paddle lever for easy on-off control
- The lock-off button is positioned in the center of the paddle lever so that it is operable no matter what portion of the lever is gripped.





Angle Grinder	9565P 125mm (5")		325
Double Insulation	Continuous rating Input	1,100W	
	Wheel diameter No load speed (rpm)	125mm (5") 12,000	
	Dimensions	307x139x103mm	
	(LxWxH)	(12-1/8"x5-1/2"x4")	
	Net Weight	2.4kg (5.2lbs)	
	Power supply cord	2.5m (8.2ft)	
	Standard Equipment: Lock Nut Wrench, Side Grip (To	ol does not come with depressed center w	heel.)

weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

