



Cordless Air Compressor AC001G



XGT
40V **Li-ion**
max

Low noise

68 dB(A)

Tank capacity

7.6 L

Max Pressure

0.93 MPa

Lightweight

Battery: BL4020-BL4080F

11.6-12.8 kg



Surrounding environment-friendly machine with low noise level

Low noise

68 dB(A)

Rigid roll cage frame construction

minimizes the chance of damage to the motor and compression units.

Carrying handle

with rubberized grip designed for easy transportation



Air filter (air intake)



Oil-free pump design

Powered by 40Vmax XGT Li-Ion battery



BL MOTOR

High operating efficiency motor

One outlet (coupler)

Air tank capacity: 7.6L

Max air pressure in tank: 0.93MPa

The cut-in pressure is 0.72MPa

Charging Time

	Fast Charging	
	DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min
BL4025 2.5Ah	28 min	38 min
*1 BL4040 4.0Ah	45 min	67 min
*1 BL4050F 5.0Ah	50 min	85 min
*1 BL4080F 8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Air Compressor

AC001G

Tank	7.6 L (2 gal)
Cut-In Pressure	0.72 MPa (105 PSI)
Cut-Out Pressure	0.93 MPa (135 PSI)
Number of Outlets	1
Performance	34.0 L/min
Noise Level	68 dB(A)
Dimensions (L x W x H)	302x434x382 mm (11-7/8" x 17-1/8" x 15")
Net weight	11.6 - 12.8 kg (25.6 - 28.2 lbs.)

Battery & Charger Sold Separately

The weight does not include battery cartridge

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202209