

# Cordless Drywall Saw DSD180









# V-notch in base plate helps easy tracing of cutting line.



#### Dust box

catches dust that drops through the base of base cover.

# Dust connector assembly

connectable to vacuum cleaner.

## LED job light

brightly illuminates the cut line for easy cutting of workpiece in the dark place.



### Cutting depth adjustment



- Cutting depth can be adjusted to drywall thickness.
- Prevent accidental breakage of wires

#### Blade cover

protects drywall surfaces from damage/ scratches.





#### **Blades**



Compatible with both special blades for this drywall saw and option snap-off blades.

### Power by 18V Li-ion battery

with Battery fuel gauge BL1860B: 6.0Ah BL1850B: 5.0Ah BL1840B: 4.0Ah BL1830B: 3.0Ah



BL1850B

BL1820B: 2.0Ah BL1815N\*: 1.5Ah \*without Battery fuel gauge BL1815N



# **Cordless Drywall Saw DSD180**



Orbital Cutting **Dust Collecting** 



Carrying Case

Strokes Per Minute (SPM) 0 - 6,000 Length of Stroke 6 mm (1/4") Drywall: 30mm (1-3/16") Wood: 15 mm (9/16") Capacity Max Output Cutting Drywall (thickness 30mm): 2.5 m/s<sup>2</sup> 79 dB(A) Vibration Level Sound Pressure Level 79 dB(A) 263x79x291mm (10-3/8"x3-1/8"x11-3/8") BL1820B: 1.7 kg (3.8 lbs) BL1860B: 1.9kg (4.2lbs) Dimensions (LxWxH)

Standard Equipment: Blade, Blade cover, Base cover, Hex Wrench, Battery, Fast Charger

weight according to EPTA-Procedure 01/ver.2.1 Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan