



Petrol Blower EB7650TH

Satisfy Professional's Needs

MM4



High air speed/ High air volume



End nozzle 90-60
Blowing velocity-oriented



End nozzle 90-70
Blowing volume-oriented

Photo : EB7650TH

75.6cm³ 4-stroke engine No mixed fuel !!

Carrying grip

redesigned to provide a comfortable grip to user's hand and an optimal center of gravity to the machine during transport



Photo : EB7650TH

Tube-mounted throttle
EB7650TH

MM4

Anti-static


- User's hand is protected from static electric shock thanks to the enough insulation distance created between grip position and nozzle.
- Static electricity can be removed by:
 - Atmospheric discharge from the wire laid inside the nozzle
 - Discharge by grounding the wire from the engine

Anti-icing

You can open the anti-icing valve by simply turning a dial to supply warm air from the engine to prevent the carburetor from icing up under cold environments.

Low vibration

- Vibration on the back of operator is reduced by the 4 damper springs mounted between the engine and the backpack frame.
- Vibration at the handle is significantly reduced by effectively damping transmission of vibration from the engine to the nozzle.



Comfortable backpack harness

- Cushioning back padding and shoulder straps are well-ventilated for effective sweat evaporation.
- Adjust straps to provide a perfect fit for every user.



Accessories

Oil bottle set
220ml
10W-30



Part No. 195532-1

Flat nozzle



Part No. 196911-6

Hip belt



Part No. 196956-4

End nozzle 90-60
Blowing velocity-oriented



Part No. 454896-5

Long pipe 90 set



Part No. 454895-7

End nozzle 90-70
Blowing volume-oriented



Part No. 455128-3

Short pipe 90 set



Part No. 196912-4

Petrol Blower

EB7650TH 75.6mL 4-stroke

- Anti Vibration
- Primer Pump
- Capacitor Discharge Ignition
- Auto Decompression

| | EB7650TH |
|------------------------|--|
| Displacement | 75.6mL |
| Fuel tank | 1.9L |
| Max. air volume | 19m ³ /min (1,140m ³ /h) |
| Max. air velocity | 89m/s |
| Sound pressure level | 100dB(A) |
| Sound power level | 110dB(A) |
| Vibration level | 2.3m/s ² |
| Dimensions (L x W x H) | 332x460x480mm |
| Net weight | (13-1/8"x18-1/8"x18-7/8") 10.8kg (23.8lbs) |

Net weight: without fuel with blower pipe, Overall length: Without blower pipes

Standard Equipment:

Oil bottle set, Box wrench 16, Driver, Flexible pipe, Swivel pipe, Hose clamp, End nozzle 90-60, End nozzle 90-70, Flat nozzle 90, Long pipe 90

weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore,
Auckland 0745
Fax 0800 600 601 Sales 09 4798251

Visit our website for information and tool features :
www.makita.co.nz