



Hammer Drill HP1630 / HP1631 16 mm (5/8")



HIGH PERFORMANCE

with Cylinder-shaped motor housing and aluminum gear housing cover

HIGH POWER 710W MOTOR Trakita








Sturdy Aluminum Gear Housing Cover

Dual-operation Mode: Rotation only / Hammering with rotation



Sturdy Cylinder-shaped Motor Housing



Continuous Rating Input: 710W

The highest in this class

Variable Speed Control Switch with F/R Change Lever



Rubberized Soft Grip Provides more control and comfort.



Photo: HP1631





	HP1631/ HP1630	16mm (5/8")	85 M
		HP1630	HP1631
	Continuous rating Input	710W	710W
	Capacity	Concrete: 16mm (5/8")	Concrete : 16mm (5/8")
		Steel : 13mm (1/2")	Steel : 13mm (1/2")
		Wood: 30mm (1-3/16")	Wood : 30mm (1-3/16")
	Impacts per minute (ipm)	0-48,000	0-48,000
	No load speed (rpm)	0-3,200	0-3,200
	Dimensions	296 x 75 x 204mm	295 x 75 x 204mm
	(L x W x H)	(11-5/8" x 2-15/16" x 8")	(11-5/8" x 2-15/16" x 8")
	Net weight	1.9kg (4.2lbs)	1.9kg (4.2lbs)
	Power supply cord	2.0m (6.6ft)	2.0m (6.6ft)

Standard Equipment Side grip, Chuck key (HP1630 only)

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan