



Makita[®]

Circular Saw
HS7601 190mm (7-1/2")

Satisfy Professional's Needs

Compact and lightweight

1,200W

Continuous rating input

Two-finger trigger switch

Soft grip
provides more comfort

Flat Motor Housing Design
increases stability when changing blades.



Aluminum plate base

Aluminum diecast safety cover

1,200W

Continuous rating input

1 Rear dust exhaust port

exhausts sawdust backward only, preventing it from scattering around to provide comfortable operation.



Dust nozzle can be attached for use with a vacuum cleaner.

2 Single action lever

for quick adjustment of cutting depth



3 Rear angular guide

For smooth and precise adjustment of bevel angle

Compatible with Guide rail

For use with Guide rail, the shape of base is designed to install Guide rail adapter.



Optional Guide rail adapter
Part No. 197005-0

Rear angular guide

Compact and lightweight

Much more compact and lightweight than the predecessor model

Model No.	Overall length (mm)	Net weight (kg)
HS7601	309	4.0
Predecessor Model	345	4.9

Circular Saw

HS7601 190mm (7-1/2")

303

- Double Insulation
- Dust Collecting

Continuous rating Input	1,200W
Max cutting capacity	at 0 degrees : 66mm (2-5/8") at 45 degrees : 46mm (1-13/16")
Blade diameter	190mm (7-1/2")
No load speed (rpm)	5,200
Dimensions (LxWxH)	309x232x255 (12-1/8"x9-1/8"x10")
Net weight	4.0kg (8.8lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment :

TCT saw blade, Hex wrench, Guide rule (Rip fence), Dust nozzle

weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore, Auckland 0745
Fax 0800 600 601 Sales 09 479 8251

Visit our website for information and tool features :
www.makita.co.nz