Satisfy Professional's Needs











High durability specificatio specially designed for 40Vmax Li-Ion batteries



4-LED fuel gauge indicator

Accessories
Shoulder hook set
Part No. GM00001028

ML002G only



The weight may differ depending on the attachment(s), including the battery cartridge. Items of standard equipment and specifications may vary by country or area.



Up to: 55

at 1m from the light source:

w/BL4025: 281 x 88 x 121 mm

(11-1/8 x 3-1/2 x 4-3/4") w/ BL4040: 287 x 88 x 136 mm

(11-1/4 x 3-1/2 x 5-3/8") 0.28 - 1.3 kg (0.62 - 2.9 lbs.)

160 lm

3.000 lx

Waterproof Triple-layer Structure



High Rigidity Battery Rails

**Cordless Worklight** 

Shock absorption structure

Cordles	s Flashlight

ML001G

Run Time (hrs) Luminous Flux Illuminance Dimensions (L x W x H)

Net weight

Standard Equipment : Strap Hook

**ML002G** Run Time (hrs) Up to: 51 Main light (on bar side): Luminous Flux Full brightness: 710 lm / Half brightness: 340 lm Illuminance Full brightness: 340 lx / Half brightness: 310 lx Sub light (on top side): Luminous Flux 130 lm Illuminance 1,900 lx w/o Battery: 376 x 86 x 137 mm (14-3/4 x 3-3/8 x 5-3/8") Dimensions (L x W x H) 0.46 - 1.5 kg (1.0 - 3.3 lbs.) Net weight

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan PRINTED IN JAPAN 202012