






Multifaceted reflector enables to illuminate evenly and Zoom function



Multifaceted reflector enables to illuminate evenly



Only center is bright

Entire circle is in uniform brightness

Zoom function



12 position pivoting flashlight head



Strap hook



Continuous illumination (approx) on a single full battery charge: hours

ML106

BL1016	5
BL1021B	6
BL1041B	12

Magnet attachment nut for optional magnet attachment

Part No. GM00001683(EU) Part No. GM00001714



(ML106 Only)



The Addie



DML808

 BL1815N
 7.5

 BL1820B
 10

 BL1830B
 14

 BL1840B
 20

 BL1850B
 26

 BL1860B
 32



Cordless LED Flashlight

ML106 12V max / DML808 18V, 14.4V

ML106

290x66x93 mm (11-3/8"x2-5/8"x3-5/8") 0.61 - 0.78 kg (1.3 - 1.7 lbs)

Up to: 12 190 lm at 1m from the light source 170 - 4,500 lx w/ BL1016/BL1021B: 271x66x93 mm (10-5/8"x2-5/8"x3-5/8") w/ BL1041B:

Net weight

Run Time (hrs)

Luminous flux

Illuminance Dimensions

 $(L \times W \times H)$

Battery & Charger Sold Separately

Standard Equipment : Strap Hook

K The weight may differ depending on the attachment(s), including the battery cartridge. The liahtest

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

at 1m from the light source 170 - 4,500 lx w/ BL1815N / BL1820B:

280x79x101 mm (11"x3-1/8"x4") w/ BL1830B / BL1840B / BL1850B / BL1860B:

297x79x119 mm (11-3/4"x3-1/8"x4-11/16") 0.73 - 1.09 kg (1.6 - 2.4 lbs)

DML808

Up to: 32

190 lm

UMHON

анали патниом

Makita Corporation