



Chain Saw UC3541A/ UC4041A



Photo: UC4041A

Tool-less saw chain/ tension adjustment

350mm (14") UC3541A/ 400mm (16") UC4041A

New adjustment lever for easier tool-less saw chain/ tension adjustment



Soft rear-handle

Easy-to-grip Front loop handle
The whole shape is firmly held, especially when the machine is tilted sideways.

Photo : UC3541A



1. extendable to allow for:
 - Easier saw chain tightening
 - Higher tightening torque
2. can be quickly retracted at any angle.
3. reduces the projections on Sprocket cover than ever.



Improved oil pump

keeps the delivery of chain oil constant regardless of temperature and the oil viscosity.



Large view window of Oil tank

allows operator to easily check oil level.



Large separate-type metal spike bumper

An optimum design has been achieved by employing separate-type. The spike grips workpiece firmly to provide more control.

Chain Saw

UC3541A 350mm (14"), **UC4041A** 400mm (16")

153

- Double Insulation
- Brake
- Automatic Oiling
- Chain Brake

Dimensions :
excluding blade and guide bar



Continuous rating input	1,800W
Chain speed per minute	870m/min (2,900ft/min)
Guide bar length	UC3541A : 350mm (14") UC4041A : 400mm (16")
Chain blade	Pitch : 3/8" Gauge : 0.043" / 0.050"
Dimensions (L x W x H)	455x245x200mm (17-7/8"x9-5/8"x7-7/8")
Net Weight*	UC3541A : 4.7kg (10.3lbs) / 4.8kg (10.5lbs) UC4041A : 4.7kg (10.5lbs) / 4.8kg (10.6lbs)
Power supply cord	0.3m (0.98ft)

Standard Equipment :
Chain Blade, Guide Bar Cover, Hook Complete

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore
Auckland 0745
Fax 0800 600 601 Sales 09 479825

Visit our website for information and tool features :
www.makita.co.nz

New adjustment lever for easier tool-less saw chain/ tension adjustment



Easy-to-grip Front loop handle
The whole shape is firmly held, especially when the machine is tilted sideways.

Photo : UC3541A

Soft rear-handle



1. extendable to allow for:
 - Easier saw chain tightening
 - Higher tightening torque
2. can be quickly retracted at any angle.
3. reduces the projections on Sprocket cover than ever.



Improved oil pump

keeps the delivery of chain oil constant regardless of temperature and the oil viscosity.



Large view window of Oil tank

allows operator to easily check oil level.



Large separate-type metal spike bumper

An optimum design has been achieved by employing separate-type. The spike grips workpiece firmly to provide more control.

Chain Saw

UC3541A 350mm (14"), **UC4041A** 400mm (16")

153

- Double Insulation
- Brake
- Automatic Oiling
- Chain Brake

Dimensions :
excluding blade and guide bar



Continuous rating input	1,800W
Chain speed per minute	870m/min (2,900ft/min)
Guide bar length	UC3541A : 350mm (14") UC4041A : 400mm (16")
Chain blade	Pitch : 3/8" Gauge : 0.043" / 0.050"
Dimensions (L x W x H)	455x245x200mm (17-7/8"x9-5/8"x7-7/8")
Net Weight*	UC3541A : 4.7kg (10.3lbs) / 4.8kg (10.5lbs) UC4041A : 4.7kg (10.5lbs) / 4.8kg (10.6lbs)
Power supply cord	0.3m (0.98ft)

Standard Equipment :
Chain Blade, Guide Bar Cover, Hook Complete

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore
Auckland 0745
Fax 0800 600 601 Sales 09 479825

Visit our website for information and tool features :
www.makita.co.nz