



Chain Saw
UC3541A/ UC4041A



Higher Tension Torque



Easy-to-grip Front loop handle
The whole shape is firmly held, especially when the machine is tilted sideways.

Soft rear-handle



Photo : UC3541A



Improved oil pump

keeps the delivery of chain oil constant regardless of temperature and the oil viscosity.



Large view window of Oil tank

allows operator to easily check oil level.



Large separate-type metal spike bumper

An optimum design has been achieved by employing separate-type. The spike grips workpiece firmly to provide more control.

Chain Saw

UC3541A 350mm (14"), UC4041A 400mm (16")

153

- Double Insulation
- Brake
- Automatic Oiling
- Chain Brake

Dimensions :
excluding blade and guide bar



Continuous rating input	1,800W
Chain speed per minute	870m/min (2,900ft/min)
Guide bar length	UC3541A : 350mm (14") UC4041A : 400mm (16")
Chain blade	Pitch : 3/8" Gauge : 0.043" / 0.050"
Dimensions (L x W x H)	455x245x200mm (17-7/8"x9-5/8"x7-7/8")
Net Weight*	UC3541A : 4.7kg (10.3lbs) / 4.8kg (10.5lbs) UC4041A : 4.7kg (10.5lbs) / 4.8kg (10.6lbs)
Power supply cord	0.3m (0.98ft)

Standard Equipment :
Chain Blade, Guide Bar Cover, Hook Complete

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore,
Auckland 0745
Fax 0800 600 601 Sales 09 4798251

Visit our website for information and tool features :
www.makita.co.nz